

GRAND CHEROKEE WK & WK2

ARB DELUXE BULL BARS & WINCH BARS

| YEAR | MODEL | FEATURES | WINCHES | PART NO. |
|-------------|------------|---|---|----------------------------|
| 2014-16 WK2 | DELUXE BAR | AIRBAG APPROVED, RECESSED INDICATORS, OPTIONAL FOG LIGHT PROVISION ¹ , TOW POINTS, SPLIT PAN, WORKS WITH PARK SENSORS ² , BLACK | HS9500, XD9000, M8000, 9.5XP, ZEON ⁴ | 3450420 ^{1,2,3,4} |
| 2011-13 WK2 | DELUXE BAR | AIRBAG APPROVED, RECESSED INDICATORS, OPTIONAL FOG LIGHT PROVISION ¹ , TOW POINTS, SPLIT PAN, WORKS WITH PARK SENSORS ² , BLACK | HS9500, XD9000, M8000, 9.5XP, ZEON ⁴ | 3450410 ^{1,2,3,4} |
| 2005-07 WK | DELUXE BAR | AIRBAG APPROVED, RECESSED INDICATORS, FACTORY FOG LIGHT PROVISION, TOW POINTS, SPLIT PAN, BLACK | HS9500, XD9000, M8000, 9.5XP, ZEON ⁴ | 3450130 ⁴ |

- ¹ OPTIONAL FOG LIGHT KIT PART NUMBER 6821201 AVAILABLE. HARNESS REQUIRED IF VEHICLE NOT FITTED WITH FACTORY FOG LIGHTS.
² ADDITIONAL FITTING KIT P/N 3550110 REQUIRED WHEN FITTING BUMPER TO VEHICLE EQUIPPED WITH FACTORY PARKING SENSORS AND RADAR.
³ WINCH INSTALL KIT PART NUMBER 3540050 REQUIRED WHEN FITTING WINCH
⁴ WARN KIT PART NUMBER W89965 REQUIRED WHEN FITTING WARN ZEON WINCH

IPF LIGHTING & ACCESSORIES

| YEAR | RECOMMENDED LIGHTING |
|---------|---|
| 2005-16 | ARB INTENSITY LED, 800XSD, 900XSD, 900XSS, 901HIDD, 901HIDS, 868CS, 968CSG, |

SAFARI SNORKEL

| YEAR | RECOMMENDED SNORKEL | PART NO. |
|------|---------------------|----------|
| | TBA | TBA |

OLD MAN EMU SUSPENSION SYSTEMS

| MODEL | LOCATION | DESCRIPTION | TYPE | LIFT | QUANTITY | PART NO. | |
|------------|---------------------------------|--|-----------------------------------|--------|----------|--------------------|--------------------|
| 2005-10 WK | FRONT | MEDIUM LOAD | SPRING | 2.0" | 1 | 2990 | |
| | | | STRUT | | 2 | *N219S/N188S | |
| | FRONT | HEAVY LOAD (90-200LBS) | SPRING | 2.0" | 1 | 2991 | |
| | | | STRUT | | 2 | *N219S/N188S | |
| | REAR | MEDIUM LOAD | SPRING | 2.0" | 1 | 2992 | |
| | | | SHOCK | | 2 | *N220/N190 | |
| | REAR | HEAVY LOAD (90-200LBS) | SPRING | 2.0" | 1 | 2993 | |
| | | | SHOCK | | 2 | *N220/N190 | |
| | 2011-15 WK2 V6 GAS ENGINE | FRONT | LIGHT LOAD - NO ARB BUMPER | SPRING | 1.75" | 1 | 3070 |
| | | | | STRUT | | 2 | 90026 ¹ |
| | | MEDIUM LOAD - WITH ARB BUMPER - NO WINCH | SPRING | 1.75" | 1 | 3059 | |
| | | | STRUT | | 2 | 90026 ¹ | |
| | | HEAVY LOAD - WITH ARB BUMPER AND WINCH | SPRING | 1.75" | 1 | 3072 | |
| | | | STRUT | | 2 | 90026 ¹ | |
| OPTIONAL | | | FRONT TRIM PACKER - GAS OR DIESEL | | | | FK79 |

- OLD MAN EMU SUSPENSION CONTINUED NEXT PAGE -

GRAND CHEROKEE WK & WK2

| OLD MAN EMU SUSPENSION SYSTEMS | | | | | | | | |
|--|---------------------------|---|--|--------|----------|----------------------|------|------|
| MODEL | LOCATION | DESCRIPTION | TYPE | LIFT | QUANTITY | PART NO. | | |
| 2011-15 WK2 DIESEL & HEMI V8 GAS | FRONT | LIGHT LOAD - NO ARB BUMPER | SPRING | 1.75" | 1 | 3073 | | |
| | | | STRUT | | 2 | 90026 ¹ | | |
| | | MEDIUM LOAD - WITH ARB BUMPER - NO WINCH | SPRING | 1.75" | 1 | 3086 | | |
| | | | STRUT | | 2 | 90026 ¹ | | |
| | | HEAVY LOAD - WITH ARB BUMPER & WINCH | SPRING | 1.75" | 1 | 3085 | | |
| | | | STRUT | | 2 | 90026 ¹ | | |
| | REAR - GAS & DIESEL | MEDIUM LOAD - (NON NIVOMAT EQUIPPED REAR SHOCKS) | SPRING | 2.0" | 1 | 3074 | | |
| | | | SHOCK | | 2 | 60124 ^{2,3} | | |
| | | | HEAVY CONSTANT LOAD - 660 LBS (NON NIVOMAT EQUIPPED REAR SHOCKS) | SPRING | 2.0" | 1 | 3060 | |
| | | HEAVY CONSTANT LOAD - 660 LBS (NON NIVOMAT EQUIPPED REAR SHOCKS) | SHOCK | | 2 | 60125 ^{2,3} | | |
| | | | MEDIUM LOAD - WITH NIVOMAT EQUIPPED REAR SHOCKS | SPRING | 2.0" | 1 | 3074 | |
| | | HEAVY CONSTANT LOAD - 660 LBS (WITH NIVOMAT EQUIPPED REAR SHOCKS) | SHOCK | | 2 | 60126 ^{2,3} | | |
| | | | SHOCK | | 2 | 60127 ^{2,3} | | |
| | | OPTIONAL | FRONT TRIM PACKER - GAS OR DIESEL | | | | | FK79 |
| | | ¹ NO TOP MOUNTING BUSHINGS AND DIRT SHIELD SUPPLIED, RE-USE OE BUSHING AND DIRT SHIELD ² TOW PACKAGE OPTION USES A NIVOMAT (SELF LEVELING) SHOCK ABSORBER AND REQUIRES A SPECIFIC DESIGN REAR SHOCK. SEE ABOVE FOR CORRECT OME PART NUMBER (EITHER PART NO. 60126 OR 60127 DEPENDING ON LOAD REQUIREMENTS). ³ PLEASE NOTE: WHEN REPLACING NIVOMAT SHOCKS, YOU MUST FIT THE APPROPRIATE OME LOAD SPRING (SEE ABOVE). TO IDENTIFY WHETHER A VEHICLE HAS THE STANDARD FITMENT REAR SHOCK OR NIVOMAT SHOCK, THE OUTER BODY DIAMETER WILL NEED TO BE MEASURED: STANDARD 51MM, NIVOMAT 63MM * FIRMER VALVED SHOCK | | | | | | |

| ARB DIFFERENTIALS & ACCESSORIES | | |
|---------------------------------|---|----------|
| AXLE | DESCRIPTION | PART NO. |
| CHRYSLER 8.25" | ARB DIFFERENTIAL COVER FOR CHRYSLER 8.25" (10-BOLT COVER) - RED | 0750005 |
| CHRYSLER 8.25" | ARB DIFFERENTIAL COVER FOR CHRYSLER 8.25" (10-BOLT COVER) - BLACK | 0750005B |

| ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES | | | | | | |
|--|-------------------------------|-------------|----------------|--------|-------|-------------------|
| YEAR | AXLE | DESCRIPTION | SHAFT | SPLINE | RATIO | PART NO. |
| FRONT 2005-ON | | TBD | | | | TBD |
| REAR 2005-10 | CHRYSLER 8.25" DIA. RING GEAR | | 1.21" (30.7MM) | 29 | ALL | RD93 ¹ |
| | DANA 44A (SRT8 MODEL) | | 1.31" (33.3MM) | 30 | ALL | RD226 |
| ¹ NEW OEM DANA 35, DANA 44 & CHRYSLER 8.25" RING GEARS MAY USE 3/8", 7/16" OR 1/2" RING GEAR BOLTS. AIR LOCKER FLANGE HOLES MUST BE DRILLED OR REAMED LARGER TO SUIT 7/16" OR 1/2" BOLTS ² QUADRADRIVE TRACTION CONTROL VEHICLES REQUIRE NON-QUADRADRIVE AXLE SHAFT REPLACEMENTS FOR AIR LOCKER INSTALLATION. | | | | | | |