

ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
1997-99	WINCH BAR	SPORT - AIRBAG APPROVED, RECESSED INDICATORS, URETHANE BUFFERS, TOW POINTS, BLACK	XD9000, M8000, M6000	3435010

IPF LIGHTING & ACCESSORIES

YEAR	RECOMMENDED LIGHTING
1997-99	800XSD, 900XSD, 900XSS, 900HIDD, 900HIDS, 868CS, 968CSG

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
2000-04	FRONT	TORSION BAR	SPRING		1	303011 ¹
		NITROCHARGER SPORT SHOCK	SHOCK		2	60040
		NITROCHARGER SHOCK	SHOCK		2	N57G
2000-04	REAR	COIL SPRING - MEDIUM LOAD (0LBS TO GVW)	SPRING	1.50"	1	2911
		NITROCHARGER SHOCK	SHOCK		2	60075
	REAR	COIL SPRING - HEAVY CONSTANT	SPRING	1.50"	1	2910
		NITROCHARGER SHOCK	SHOCK		2	60075
1998-99	FRONT	TORSION BAR	SPRING		1	303011 ¹
		NITROCHARGER SPORT SHOCK	SHOCK		2	60040
		NITROCHARGER SHOCK	SHOCK		2	N57G
1998-99	REAR	REAR LEAF SPRING - MEDIUM LOAD	SPRING	1.0"	2	CS040R ²
		NITROCHARGER SPORT SHOCK	SHOCK		2	60036
1998-99	REAR	REAR LEAF SPRING - HEAVY CONSTANT (440LBS TO GVW)	SPRING	1.0"	2	CS041R ²
		NITROCHARGER SPORT SHOCK	SHOCK		2	60036
1998-99	REQ'D FOR INSTALLATION	REAR LEAF SPRING - LEAF SPRING BUSHING KIT			2	OMESB83 ²
	OPTIONAL	REAR EXTRA LEAF				D7XL ³

¹ ADJUST FRONT TORSION BAR FOR ADDITIONAL HEIGHT AFTER INSTALLING REAR SPRINGS. SET RIDE HEIGHT TO 1/3 UPPER BUMP STOP CLEARANCE AND 2/3 LOWER BUMP STOP CLEARANCE.

² CS040R & CS041R SPRINGS CAN ONLY BE INSTALLED WITH OMESB83 BUSHINGS.

³ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
ALL	FRONT	IFS, 28 SPLINE	28.8 (1.13")	28	ALL	RD110
ALL	REAR	3.0L, 9.00" RG	30.5 (1.20")	28	ALL	RD212
ALL	REAR	3.5L, 9.50" RG	35.5 (1.40")	31	ALL	RD154