

ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
1998-03	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, URETHANE BUFFERS, TOW POINTS, BLACK	XD9000, M8000, M6000	3444070 ¹
	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, URETHANE BUFFERS, TOW POINTS, BLACK	XD9000, M8000	3444060 ²
1992-98	WINCH BAR	RECESSED INDICATORS, TOW POINTS, BLACK	XD9000, M8000, M6000	3444050

¹ ARB BAR #3444070 MEASURES 70.5" WIDE AND SUITS MODELS WITH "OVERFENDERS".

² ARB BAR #3444060 MEASURES 68" WIDE AND SUITS MODELS WITH STANDARD FENDER FLARES.

IPF LIGHTING & ACCESSORIES

YEAR	TYPE	RECOMMENDED LIGHTING
1992-03	ALL	800XSD, 901XSD, 901XSS, 901HIDD, 901HIDS, 868CS, 968CSG, ARB INTENSITY LED

SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
1992-97	3.2L, V6 SNORKEL	SS225R

REFER TO WWW.SAFARI4X4.COM.AU FOR DETAILS.

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
1992-02	FRONT	STOCK/LIGHT LOAD	TORSION	N/A	N/A	N/A
		NITROCHARGER SPORT	SHOCK		2	60031
	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	1.0"	1	2912 ²
		NITROCHARGER SPORT SHOCK	SHOCK		2	60074
	REAR	HEAVY LOAD (220LBS TO GVW)	SPRING	1.0"	1	2919
		NITROCHARGER SPORT SHOCK	SHOCK		2	60074
1982-3/92	FRONT	STOCK/LIGHT LOAD	TORSION	N/A	N/A	N/A
		NITROCHARGER SPORT SHOCK	SHOCK		2	60031
	REAR	HEAVY LOAD (440LBS TO GVW)	SPRING	.75"	2	CS028R ³
		NITROCHARGER SPORT SHOCK	SHOCK		2	60063

REQ'D FOR INSTALLATION	LEAF SPRING BUSHING KIT	2	OMESB90
	UBOLTS	4	OMEU59A

OPTIONAL	REAR EXTRA LEAF		D19XL ⁴
----------	-----------------	--	--------------------

¹ ADJUST FRONT TORSION BAR FOR ADDITIONAL HEIGHT AFTER INSTALLING REAR SPRINGS. SET RIDE HEIGHT TO 1/3 UPPER BUMP STOP CLEARANCE AND 2/3 LOWER BUMP STOP CLEARANCE.

² COIL MUST BE INSTALLED WITH PROGRESSIVE RATE TO THE TOP.

³ FOR LIGHT LOAD APPLICATIONS, THE 3RD LEAF FROM THE TOP OF THE SPRING PACK CAN BE REMOVED FOR IMPROVED RIDE COMFORT.

⁴ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

* FIRMER SHOCK.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1990 ON	FRONT	INDEPENDENT SUSPENSION, IFS	28.4 (1.12")	17	ALL	RD203
1987-91	REAR	V6 MODELS ONLY	33.5 (1.32")	26	ALL	RD213
1993-97	REAR	ALL MODELS	33.5 (1.32")	26	ALL	RD213
1998-99	REAR	NON-LSD MODELS	38.1 (1.50")	23	ALL	NA
2000 ON	REAR	LSD MODELS ¹	38.1 (1.50")	23	ALL	NA ¹

¹ THIRD MEMBER MAY BE SWAPPED FROM PRE-2000 NON-LSD MODEL FOR RD85 FITMENT.