

ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
ALL	WINCH BUMPER	AIRBAG APPROVED, TOW POINTS, BLACK	9.5T1/SI, HS9500I, XD9000, XD9000I, M8000, XP9500	3450150

ARB REAR PROTECTION BUMPER & TIRE CARRIER

YEAR	DESCRIPTION	PART NO.
ALL	DELUXE REAR BAR ASSEMBLY, D-SHACKLE EYES, HI-LIFT JACK POINTS, RECV. HITCH, BLACK	5650310 ¹
	OPTIONAL IPF BACK-UP LIGHT	8161

¹ DUE TO VARIATIONS IN CHASSIS, MODIFICATION MAY BE REQUIRED TO MOUNTING BRACKETS

SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
ALL	INLINE SIX, 4.0L, PETROL, FUEL INJECTED	SS1000HF ^{1,2}

¹ WILL NOT FIT MODELS WITH ABS BRAKING SYSTEMS

² CARBURETOR EQUIPPED 4.2 LITER REQUIRE MODIFICATIONS. 4 CYLINDER ENGINES MAY REQUIRE MODIFICATIONS

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
ALL	COMPLETE KIT	STOCK/LIGHT LOAD KIT	KIT	2"	1	OMEYJLKS ^{2,3}
		MEDIUM LOAD KIT	KIT	1.75"-2"	1	OMEYJMKS ^{2,3}
		HEAVY LOAD KIT	KIT	1.75"-2"	1	OMEYJHKS ^{2,3,7}
	FRONT	STOCK/LIGHT LOAD (0-100LBS)	SPRING	2.0"	2	CS014F ^{3,4}
		NITROCHARGER SPORT	SHOCK		2	60098
	FRONT	HEAVY LOAD (100-200LBS)	SPRING	2.0"	2	CS036R ^{3,7}
		NITROCHARGER SPORT	SHOCK		2	60098
	REAR	LIGHT LOAD/SOFT TOP	SPRING	2.0"	2	CS037R
		NITROCHARGER SPORT	SHOCK		2	60099
	REAR	MEDIUM LOAD/HARD TOP	SPRING	2.0"	2	CS036R
		NITROCHARGER SPORT	SHOCK		2	60099
	REQ'D FOR INSTALLATION	LEAF SPRING BUSHING KIT			4	OMESB57 ¹
		T-CASE SPACER KIT			1	JWVK01 ²
		STEERING DAMPER			1	OMESD40 ⁵
		STEERING DAMPER			1	OMESD48 ⁵
	OPTIONAL	GREASABLE SHACKLE KIT			2	OMEGS11
		GREASABLE BUSHING KIT			4	OMESB87 ¹
		GREASABLE PIN KIT			2	OMEGP9 ⁶
FRONT EXTRA LEAF				2	D23XL ⁴	
REAR EXTRA LEAF				2	D24XL ⁴	

¹ USE OMESB57 BUSHINGS WITH ORIGINAL SHACKLES. USE OMESB87 BUSHINGS WITH OME GREASABLE SHACKLES.

² JWVK01 IS MANDATORY TO PREVENT DRIVELINE VIBRATION IF A SLIP YOKE ELIMINATOR IS NOT INSTALLED.

³ DUE TO A VARIANCE IN CURB WEIGHT, 4 CYLINDER MODELS MAY NET SLIGHTLY MORE LIFT THAN 6 CYLINDER MODELS.

⁴ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

⁵ FOR STANDARD APPLICATIONS, USE OMESD40. FOR APPLICATIONS NEEDING FIRMER VALVING, USE OMESD48

⁶ GREASABLE PINS ARE USED AT THE FIXED END OF THE LEAF SPRING. TWO PINS PER KIT.

⁷ WHEN FITTING CS036R TO FRONT, REMOVING CASTER WEDGE IS REQUIRED PRIOR TO INSTALLATION

WRANGLER YJ

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES							
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.	
ALL	FRONT	DANA 30	29.5 (1.16")	27	3.73 & UP	RD100	
				27	3.54 & DN	RD101	
				30	3.73 & UP	RD104	
ALL	REAR	DANA 35, C-CLIP, XJ, YJ, ZJ, TJ, WJ	29.5 (1.16")	27	2.73-3.31	RD103	
				33.3 (1.31")	27	3.54 & UP	RD102 ¹
					30	3.54 & UP	RD105

¹ SOME DANA 35'S 4.10 GEAR SETS, MAY REQUIRE A HIGH SPEED CARRIER AIR LOCKER. (RD103)

ARB AIR LOCKER DIFFERENTIAL COVERS		
DIFFERENTIAL	DESCRIPTION	PART NO.
DANA 30	ARB DIFFERENTIAL COVER FOR DANA 30 - RED	0750002 ^{1,2}
DANA 30	ARB DIFFERENTIAL COVER FOR DANA 30 - BLACK	0750002B ^{1,2}
DANA 35	ARB DIFFERENTIAL COVER FOR DANA 35 - RED	0750004 ²

¹ WILL NOT WORK WITH STOCK HEIGHT VEHICLES

² INTERNAL DIFF COVER MODIFICATIONS MAY BE NECESSARY WITH SOME R&P RATIOS IF CONTACT WITH COVER OCCURS